

## TC SMART



## Overview

With its new TC5 SMART heat press, Secabo opens up new innovative paths leading to even better performance. This latest development of the successful automatic knee-lever press Secabo TC5 introduces a world novelty to the market, which opens up a variety of new options to users: The controller of the TC5 SMART now comes equipped with a Bluetooth interface that allows for controlling the press via the free app Secabo Smart Transfer, while also providing access to a comprehensive function database. This allows users to: Simply enter the type of fabric and the transfer material and immediately retrieve the matching combinations of temperature, time and pressure. Additional features, such as the calculation of heat-up times and warning functions, make the app a valuable assistant for all common heat transfer methods. The new heat press Secabo TC5 SMART offers a work surface of 38 x 38 cm, is easy to use and robust in ongoing operation. The modular design allows for quick and easy installation of removable plates in various formats, a quick change system and a slide extension.

## Features



### Bluetooth interface

The device can be connected via Bluetooth with a mobile device and the Secabo Smart Transfer App can be connected and controlled.



### Secabo Smart Transfer App

The device is designed for control by the Secabo Smart Transfer App suitable. Hilde of this app allows you to precisely match Transfer parameters for your application.



### Digital controller

Time and temperature are set within one digital controller.



### Large working area

Due to the large folding angle of 40°, the transfer objects can be aligned comfortably and precisely.



### Low hysteresis

The temperature controllers reduce temperature fluctuations to a minimum



### Variable working pressure

the pressure can easily be adjusted – depending on the technology and object



### Opens automatically

This heat press opens automatically after the the adjusted time



### Working safely

The safety and quality of the machines is permanently controlled by German safety standards



### Exact temperature distribution

The high-quality heat plate ensures an exact temperature distribution over the whole heating plate



### Exchangeable base plates

exchangeable base plates now available in combination with the quick change system

## Technical Data

|                       |                                                                                                                      |
|-----------------------|----------------------------------------------------------------------------------------------------------------------|
| pressure setting      | the heating plate can be adjusted with a hand reel                                                                   |
| net weight            | 32 kg                                                                                                                |
| working area          | 38cm x 38cm                                                                                                          |
| scope of delivery     | Mechanical base, heating plate and base plate, controller box, C13 power supply cable, tools, operating instructions |
| max. working pressure | 250 g/cm <sup>2</sup>                                                                                                |
| max. clam angle       | 40 °                                                                                                                 |
| max temperature       | 225 °C                                                                                                               |
| maximum time preset   | 999 s                                                                                                                |
| power supply          | AC voltage 230V / 50Hz - 60Hz, 1.8kW                                                                                 |
| environment           | +5°C - +35°C / 30% - 70% humidity                                                                                    |
| Dimensions closed     | 41cm x 57cm x 73cm                                                                                                   |
| Dimensions open       | 41cm x 93cm x 67cm                                                                                                   |
| Brand                 | Secabo                                                                                                               |

## Views

